

C-Power Lubrication System

Proper lubrication is critical to bearing and machine performance. To help prevent premature failures, C-Power multi-point lubricators deliver grease to up to six lubrication points. C-Power multi-point lubricators are centralized lubrication systems that can be filled with Timken-formulated lubricants or many other types of commercial lubricants. Oil is not an option in this unit. A full line of accessories – including brackets, clamps, brushes, fittings and hose extensions – ease installation and offer a host of mounting options for hard-to-reach locations.

With more than a century of leadership in developing friction management solutions, Timken is a trusted source for a broad range of bearings – and products that help keep all bearings and related components running smoothly. Turn to Timken and C-Power multi-point lubricators to help reduce friction in your industrial applications.

Timken C-Power Features:

- *Timken C-Power replaces the need for up to six single-point lubricators with one, easy to maintain multi-point system.*
- *Remote mounting addresses 'space confined lubrication points' with no pressure loss up to 16 feet per point.*
- *Versatile programmability from one to 24 months.*
- *Full pressure is maintained regardless of the number of lubrication points selected.*
- *Includes a complete kit of accessories, full instructions and enough pre-filled grease lines for six lubrication points.*

TIMKEN

Where You Turn



C-POWER

(MULTI-POINT LUBRICATOR)



Model Number	250	500
Name	250 cc	500 cc
Description	Programmable multi-point lubricator capable of lubricating up to six points. The lubricant cartridge is replaceable.	Programmable multi-point lubricator capable of lubricating up to six points. The lubricant cartridge is replaceable.
Complete Unit (XXX is the lubricant reference)	PC322XXX	PC352XXX
Lubrication Cartridge Part Number (XXX is the lubricant reference)	Replacement set (includes battery and lubricant cartridge): 8.45 fl. oz. (250 cm ³) unit: PC321XXX	Replacement set (includes battery and lubricant cartridge): 16.9 fl. oz. (500 cm ³) unit: PC351XXX
Lubrication Period	Variable according to set-up; 1 day to 24 months (battery limited)	Variable according to set-up; 1 day to 24 months (battery limited)
Max. Pressure	360 psi/25 bar	360 psi/25 bar
Application Temperature	-4° F to 140° F (-20° C to 60° C)	-4° F to 140° F (-20° C to 60° C)
Approx. Weight	3.4 lb (1.53kg)	4.0 lb (1.82kg)
Dimensions	Height: 14.3" (360 mm) Max. diameter: 3.6" (92 mm)	Height: 15.8" (400 mm) Max. diameter: 3.6" (92 mm)

TIMKEN

Where You Turn

Bearings • Steel •
Precision Components • Lubrication •
Seals • Remanufacture and Repair •
Industrial Services
www.timken.com

Timken® is a registered trademark of
The Timken Company.

©2006 The Timken Company
Printed in U.S.A.
15M 09-06-29 Order No. 10054